

## ITEM 2

### MULTÍMETRO DIGITAL

MARCA SANWA

MODELO RD701

CANTIDAD 10

ENTREGA MOQUEGUA

FORMA DE PAGO CONTRA ENTREGA



- Sistema de visualización: digital
- Tipo: portátil
- Otras características: de tensión, de corriente
- Aplicaciones: industrial
- Tensión: Mín.: 400 mV Máx.: 1000 V
- Corriente: Mín.: 0.4 mA Máx.: 10 A
- Impedancia: Mín.: 400 Ohm Máx.: 40000000 Ohm

RD701 only



RD700 / 701	Measuring range	Best accuracy	Resolution	Input impedance
DCV	400m/4/40/400/1000V	± (0.3%+4)	0.1mV	10M~1000MΩ
ACV	400m/4/40/400/1000V	± (1.5%+5)	0.1mV	
DCA	400μ/4000μ/40m/400m/4/10A	± (1.2%+3)	0.1μA	
ACA	400μ/4000μ/40m/400m/4/10A	± (1.5%+4)	0.1μA	
Resistance	400/4k/40k/400k/4M/40MΩ	± (0.6%+4)	0.1Ω	
Capacitance	500n/5μ/50μ/500μ/3000μF	± (2.5%+6)	0.01nF	
Temperature	-20°C~300°C	± (2%+3)	1°C	
Frequency	50Hz~1MHz	± (0.5%+4)	0.01Hz	
Continuity	Buzzer sounds at between 20Ω and 120Ω. Open voltage : approx. 0.4V			
Diode Test	Open voltage : approx. 1.6V			
Bandwidth	50~500Hz			
Fuse / Battery	12.5A/500V IR20kA φ6.3×32mm 0.63A/500V IR200kA φ6.3×32mm	6LF22 (9V)×1		
Size / Mass	H179×W87×D55mm/460g (including holster)			
Standard accessories included	Test Lead (TL-23a), Thermocouple K type (K-250PC), Holster (H-50), Instruction manual			